

## MULTI-PURPOSE WOOD FILLER

## SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2015/830)

## SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

## 1.1. Product identifier

Product name : MULTI-PURPOSE WOOD FILLER

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

## 1.3. Details of the supplier of the safety data sheet

Registered company name : BLANCHON.

Address : 50, 8ème rue.69800.SAINT PRIEST.FRANCE.

Telephone : 00.33.4.72.89.06.09. Fax : 00.33.4.72.89.06.02.

fds@blanchon.com

http://www.blanchon.com/

## 1.4. Emergency telephone number : 00.33.1.45.42.59.59.

Association/Organisation : Orfila (INRS).

## SECTION 2 : HAZARDS IDENTIFICATION

## 2.1. Classification of the substance or mixture

## In compliance with EC regulation No. 1272/2008 and its amendments.

May produce an allergic reaction (EUH208).

This mixture does not present a physical hazard. Refer to the recommendations regarding the other products present on the site.

This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

## 2.2. Label elements

## In compliance with EC regulation No. 1272/2008 and its amendments.

Additional labeling :

EUH208

Contains 1,2-BENZISOTHIAZOL-3(2H)-ONE. May produce an allergic reaction.

EUH208

Contains MIXTURE OF: 5-CHLORO-2-METHYL-4-ISOTHIAZOLIN-3-ONE ;  
2-METHYL-2H-ISOTHIAZOL-3-ONE (3:1). May produce an allergic reaction.

EUH210

Safety data sheet available on request.

Precautionary statements - General :

P102

Keep out of reach of children.

Precautionary statements - Prevention :

P271

Use only outdoors or in a well-ventilated area.

Precautionary statements - Disposal :

P501

Dispose of contents / container to an approved landfill.

## 2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC)  $\geq 0.1\%$  published by the European Chemicals Agency (ECHA) under article 57 of REACH: <http://echa.europa.eu/fr/candidate-list-table>

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

## SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

## 3.2. Mixtures

## Composition :

Identification	(EC) 1272/2008	Note	%
CAS: 1317-65-3 EC: 215-279-6 REACH: 01-2119486795-18  LIMESTONE		[1]	50 $\leq$ x % < 100
CAS: 13463-67-7 EC: 236-675-5 REACH: 01-2119489379-17  TITANIUM DIOXIDE		[1]	0 $\leq$ x % < 2.5

## MULTI-PURPOSE WOOD FILLER

INDEX: 613-088-00-6 CAS: 2634-33-5 EC: 220-120-9  1,2-BENZISOTHIAZOL-3(2H)-ONE	GHS05, GHS07, GHS09 Dgr Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400 M Acute = 1		0 <= x % < 1
CAS: 55965-84-9 EC: 611-341-5  MIXTURE OF: 5-CHLORO-2-METHYL-4-ISOTHIAZOLIN-3-ONE ; 2-METHYL-2H-ISOTHIAZOL-3-ONE (3:1)	GHS06, GHS05, GHS09 Dgr Met. Corr. 1, H290 Acute Tox. 3, H311 Skin Corr. 1B, H314 Skin Sens. 1, H317 Eye Dam. 1, H318 Acute Tox. 2, H330 Aquatic Acute 1, H400 M Acute = 10 Aquatic Chronic 1, H410 M Chronic = 10		0 <= x % < 1

(Full text of H-phrases: see section 16)

**Information on ingredients :**

[1] Substance for which maximum workplace exposure limits are available.

**SECTION 4 : FIRST AID MEASURES**

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

**4.1. Description of first aid measures****In the event of exposure by inhalation :**

In the event of an allergic reaction, seek medical attention.

**In the event of splashes or contact with skin :**

In the event of an allergic reaction, seek medical attention.

**In the event of swallowing :**

Seek medical attention, showing the label.

**4.2. Most important symptoms and effects, both acute and delayed**

No data available.

**4.3. Indication of any immediate medical attention and special treatment needed**

No data available.

**SECTION 5 : FIREFIGHTING MEASURES**

Non-flammable.

**5.1. Extinguishing media****Suitable methods of extinction**

In the event of a fire, use :

- sprayed water or water mist
- foam
- multipurpose ABC powder
- BC powder
- carbon dioxide (CO2)

**Unsuitable methods of extinction**

In the event of a fire, do not use :

- water jet

**5.2. Special hazards arising from the substance or mixture**

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO2)

## MULTI-PURPOSE WOOD FILLER

**5.3. Advice for firefighters**

No data available.

**SECTION 6 : ACCIDENTAL RELEASE MEASURES****6.1. Personal precautions, protective equipment and emergency procedures**

Consult the safety measures listed under headings 7 and 8.

**For first aid worker**

First aid workers will be equipped with suitable personal protective equipment (See section 8).

**6.2. Environmental precautions**

Prevent any material from entering drains or waterways.

**6.3. Methods and material for containment and cleaning up**

Clean preferably with a detergent, do not use solvents.

**6.4. Reference to other sections**

No data available.

**SECTION 7 : HANDLING AND STORAGE**

Requirements relating to storage premises apply to all facilities where the mixture is handled.

**7.1. Precautions for safe handling**

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

**Fire prevention :**

Prevent access by unauthorised personnel.

**Recommended equipment and procedures :**

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

**Prohibited equipment and procedures :**

No smoking, eating or drinking in areas where the mixture is used.

**7.2. Conditions for safe storage, including any incompatibilities**

No data available.

**Storage**

Keep out of reach of children.

**Packaging**

Always keep in packaging made of an identical material to the original.

**7.3. Specific end use(s)**

No data available.

**SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION****8.1. Control parameters****Occupational exposure limits :**

- ACGIH TLV (American Conference of Governmental Industrial Hygienists, Threshold Limit Values, 2010) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
13463-67-7	10 mg/m <sup>3</sup>			A4	

- France (INRS - ED984 :2016) :

CAS	VME-ppm :	VME-mg/m <sup>3</sup> :	VLE-ppm :	VLE-mg/m <sup>3</sup> :	Notes :	TMP No :
1317-65-3	-	10	-	-	-	-
13463-67-7	-	10	-	-	-	-

- UK / WEL (Workplace exposure limits, EH40/2005, 2011) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
1317-65-3	- ppm 4 mg/m <sup>3</sup>	- ppm - mg/m <sup>3</sup>			
13463-67-7	- ppm 4 mg/m <sup>3</sup>	- ppm - mg/m <sup>3</sup>			

**Derived no effect level (DNEL) or derived minimum effect level (DMEL):**

TITANIUM DIOXIDE (CAS: 13463-67-7)

## MULTI-PURPOSE WOOD FILLER

**Final use:**

Exposure method:  
Potential health effects:  
DNEL :

**Workers.**

Inhalation.  
Long term local effects.  
10 ppm

**Final use:**

Exposure method:  
Potential health effects:  
DNEL :

**Consumers.**

Ingestion.  
Long term systemic effects.  
700 mg/kg body weight/day

**Predicted no effect concentration (PNEC):**

TITANIUM DIOXIDE (CAS: 13463-67-7)

Environmental compartment:  
PNEC : Air.  
1667 mg/kg

Environmental compartment:  
PNEC : Soil.  
100 mg/kg

Environmental compartment:  
PNEC : Fresh water.  
0.184 mg/l

Environmental compartment:  
PNEC : Sea water.  
0.0184 mg/l

Environmental compartment:  
PNEC : Intermittent waste water.  
0.61 mg/l

Environmental compartment:  
PNEC : Fresh water sediment.  
1000 mg/kg

Environmental compartment:  
PNEC : Marine sediment.  
100 mg/kg

Environmental compartment:  
PNEC : Waste water treatment plant.  
100 mg/l

**8.2. Exposure controls****Personal protection measures, such as personal protective equipment**

Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE) :



Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

**- Eye / face protection**

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles in accordance with standard EN166.

**- Hand protection**

Wear suitable protective gloves in the event of prolonged or repeated skin contact.

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN374.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Recommended properties :

- Impervious gloves in accordance with standard EN374

**- Body protection**

## MULTI-PURPOSE WOOD FILLER

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

## SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

## 9.1. Information on basic physical and chemical properties

## General information :

Physical state : Paste.

## Important health, safety and environmental information

pH : 7.00 .  
Neutral.

Boiling point/boiling range : 100 °C.

Flash point interval : Not relevant.

Vapour pressure (50°C) : Below 110 kPa (1.10 bar).

Density : > 1

Water solubility : Soluble.

Melting point/melting range : Not specified.

Self-ignition temperature : Not specified.

Decomposition point/decomposition range : Not specified.

## 9.2. Other information

V.O.C. <= 50 g/l.

## SECTION 10 : STABILITY AND REACTIVITY

## 10.1. Reactivity

No data available.

## 10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

## 10.3. Possibility of hazardous reactions

No data available.

## 10.4. Conditions to avoid

## 10.5. Incompatible materials

## 10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)

- carbon dioxide (CO<sub>2</sub>)

## SECTION 11 : TOXICOLOGICAL INFORMATION

## 11.1. Information on toxicological effects

No data available.

## 11.1.1. Substances

## Acute toxicity :

MIXTURE OF: 5-CHLORO-2-METHYL-4-ISOTHIAZOLIN-3-ONE ; 2-METHYL-2H-ISOTHIAZOL-3-ONE (3:1) (CAS: 55965-84-9)

Oral route : LD50 = 550 mg/kg  
Species : Rat

Dermal route : 200 < LD50 <= 400 mg/kg  
Species : Rat

Inhalation route (n/a) : LC50 0.31 mg/l  
Species : Rat  
Duration of exposure : 4 h

TITANIUM DIOXIDE (CAS: 13463-67-7)

Oral route : LD50 > 5000 mg/kg  
Species : Rat

## MULTI-PURPOSE WOOD FILLER

OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down Procedure)

Dermal route : LD50 > 5000 mg/kg  
Species : Rabbit

Inhalation route (n/a) : LC50 > 6.82 mg/l  
Species : Rat

LIMESTONE (CAS: 1317-65-3)  
Oral route : LD50 = 6450 mg/kg  
Species : Rat

Dermal route : LD50 = 500 mg/kg  
Species : Rabbit

**Skin corrosion/skin irritation :**

TITANIUM DIOXIDE (CAS: 13463-67-7)

OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

MIXTURE OF: 5-CHLORO-2-METHYL-4-ISOTHIAZOLIN-3-ONE ; 2-METHYL-2H-ISOTHIAZOL-3-ONE (3:1) (CAS: 55965-84-9)  
Corrosivity : Causes severe skin burns.

**Serious damage to eyes/eye irritation :**

TITANIUM DIOXIDE (CAS: 13463-67-7)

OECD Guideline 405 (Acute Eye Irritation / Corrosion)

**Respiratory or skin sensitisation :**

MIXTURE OF: 5-CHLORO-2-METHYL-4-ISOTHIAZOLIN-3-ONE ; 2-METHYL-2H-ISOTHIAZOL-3-ONE (3:1) (CAS: 55965-84-9)

May cause an allergic skin reaction.

Local lymph node stimulation test : Sensitiser.  
Species : Guinea pig

TITANIUM DIOXIDE (CAS: 13463-67-7)

OECD Guideline 406 (Skin Sensitisation)

**Specific target organ systemic toxicity - repeated exposure :**

TITANIUM DIOXIDE (CAS: 13463-67-7)

Oral route : C = 3500 mg/kg bodyweight/day  
Species : Rat  
Duration of exposure : 90 days

Inhalation route : C = 10 mg/litre/6h/day  
Species : Rat  
Duration of exposure : 90 days

**11.1.2. Mixture****Respiratory or skin sensitisation :**

Contains at least one sensitising substance. May cause an allergic reaction.

**Monograph(s) from the IARC (International Agency for Research on Cancer) :**

CAS 13463-67-7 : IARC Group 2B : The agent is possibly carcinogenic to humans.

## SECTION 12 : ECOLOGICAL INFORMATION

**12.1. Toxicity****12.1.1. Substances**

MIXTURE OF: 5-CHLORO-2-METHYL-4-ISOTHIAZOLIN-3-ONE ; 2-METHYL-2H-ISOTHIAZOL-3-ONE (3:1) (CAS: 55965-84-9)

Fish toxicity : 0.01 < LC50 <= 0.1 mg/l  
Factor M = 10

Crustacean toxicity : 0.01 < EC50 <= 0.1 mg/l

## MULTI-PURPOSE WOOD FILLER

Factor M = 10

Algae toxicity :  
0.01 < EC<sub>50</sub> ≤ 0.1 mg/l  
Factor M = 10

## TITANIUM DIOXIDE (CAS: 13463-67-7)

Fish toxicity :  
LC<sub>50</sub> > 100 mg/l  
Species : Oncorhynchus mykiss  
Duration of exposure : 96 h

Crustacean toxicity :  
EC<sub>50</sub> > 100 mg/l  
Species : Daphnia magna  
Duration of exposure : 48 h

Algae toxicity :  
EC<sub>50</sub> = 16 mg/l  
Species : Pseudokirchnerella subcapitata  
Duration of exposure : 72 h

## LIMESTONE (CAS: 1317-65-3)

Fish toxicity :  
LC<sub>50</sub> > 10000 mg/l  
Species : Oncorhynchus mykiss  
Duration of exposure : 96 h

Crustacean toxicity :  
EC<sub>50</sub> > 1000 mg/l  
Species : Daphnia magna  
Duration of exposure : 48 h

Algae toxicity :  
EC<sub>50</sub> > 200 mg/l  
Species : Desmodesmus subspicatus  
Duration of exposure : 72 h

**12.1.2. Mixtures**

No aquatic toxicity data available for the mixture.

**12.2. Persistence and degradability****12.2.1. Substances**

MIXTURE OF: 5-CHLORO-2-METHYL-4-ISOTHIAZOLIN-3-ONE ; 2-METHYL-2H-ISOTHIAZOL-3-ONE (3:1) (CAS: 55965-84-9)

Biodegradability : Non-rapidly degradable.

TITANIUM DIOXIDE (CAS: 13463-67-7)

Biodegradability : Non-rapidly degradable.

LIMESTONE (CAS: 1317-65-3)

Biodegradability : no degradability data is available, the substance is considered as not degrading quickly.

**12.3. Bioaccumulative potential****12.3.1. Substances**

TITANIUM DIOXIDE (CAS: 13463-67-7)

Octanol/water partition coefficient : log K<sub>ow</sub> < 3.**12.4. Mobility in soil**

No data available.

**12.5. Results of PBT and vPvB assessment**

No data available.

**12.6. Other adverse effects**

No data available.

**MULTI-PURPOSE WOOD FILLER**

**SECTION 13 : DISPOSAL CONSIDERATIONS**

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

**13.1. Waste treatment methods**

Do not pour into drains or waterways.

**Waste :**

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

**Soiled packaging :**

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

**SECTION 14 : TRANSPORT INFORMATION**

Exempt from transport classification and labelling.

**14.1. UN number**

-

**14.2. UN proper shipping name**

-

**14.3. Transport hazard class(es)**

-

**14.4. Packing group**

-

**14.5. Environmental hazards**

-

**14.6. Special precautions for user**

-

**SECTION 15 : REGULATORY INFORMATION**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**- Classification and labelling information included in section 2:**

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2017/776 (ATP 10)

**- Container information:**


No data available.

**- Particular provisions :**

No data available.

**- Standardised American system for the identification of hazards presented by the product in view of emergency procedures (NFPA 704) :**

NFPA 704, Labelling: Health=0 Inflammability=1 Instability/Reactivity=1 Specific Risk=none



**15.2. Chemical safety assessment**

No data available.



**MULTI-PURPOSE WOOD FILLER**

**SECTION 16 : OTHER INFORMATION**

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

FOR PROFESSIONAL USE ONLY

**Wording of the phrases mentioned in section 3 :**

H290	May be corrosive to metals.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H330	Fatal if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

**Abbreviations :**

DNEL : Derived No-Effect Level

PNEC : Predicted No-Effect Concentration

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefährdungsklasse (Water Hazard Class).

PBT: Persistent, bioaccumulable and toxic.

vPvB : Very persistent, very bioaccumulable.

SVHC : Substances of very high concern.