

SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2020/878)

SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name : LIBERON - BEESWAX - Dark - 150 mL

Product code : 126895

1.2. Relevant identified uses of the substance or mixture and uses advised against

Wax

Use descriptor system (REACH) :

Paints, varnishes and related products coating with layered application.

1.3. Details of the supplier of the safety data sheet

Registered company name : LIBERON Ltd

Address : .Mountfield Industrial Estate. KENT TN28 8XU NEW ROMNEY GB

Telephone : + (44) 1797 367 555. Fax: + (44) 1797 367 575. Telex: .

fds.produits@v33.com

www.liberon.co.uk / Head Office - V33 Group - Rue de la Croix Bernard - BP1 - 39210 DOMBLANS cedex - FRANCE - Tel: +33 3 84 35 00 33

1.4. Emergency telephone number : .

Association/Organisation : .

Other emergency numbers

UK/NL: 111 - Emergency Action: In the event of a medical enquiry involving this product, please contact your doctor or local hospital accident and emergency department.

Republic of Ireland : +353 (0)1 809

2166 - Emergency medical information: 8am-10pm (seven days) contact NPIC, Beaumont Hospital, Dublin 9 DOV2NO, Ireland.

SECTION 2 : HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

Flammable liquid, Category 3 (Flam. Liq. 3, H226).

Skin irritation, Category 2 (Skin Irrit. 2, H315).

Eye irritation, Category 2 (Eye Irrit. 2, H319).

Skin sensitisation, Category 1 (Skin Sens. 1, H317).

Specific target organ toxicity (single exposure), Category 3 (STOT SE 3, H336).

Hazardous to the aquatic environment - Chronic hazard, Category 3 (Aquatic Chronic 3, H412).

2.2. Label elements

In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms :



GHS02



GHS07

Signal Word :

WARNING

Product identifiers :

EC 919-857-5

HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS

650-002-00-6

TURPENTINE, OIL

Hazard statements :

H226

Flammable liquid and vapour.

H315

Causes skin irritation.

H317

May cause an allergic skin reaction.

H319

Causes serious eye irritation.

H336

May cause drowsiness or dizziness.

H412

Harmful to aquatic life with long lasting effects.

Precautionary statements - General :

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
Precautionary statements - Prevention :
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection/
...
Precautionary statements - Response :
P302 + P352 IF ON SKIN: Wash with plenty of water/...
Precautionary statements - Disposal :
P501 Dispose of contents/container to a waste collection center (contact the local authority)

2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) $\geq 0.1\%$ published by the European Chemicals Agency (ECHA) under article 59 of REACH: <http://echa.europa.eu/fr/candidate-list-table>
The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.
The mixture does not contain substances $\geq 0.1\%$ with endocrine disrupting properties in accordance with the criteria of the Delegated Regulation (EU) 2017/2100 of the Commission or Regulation (EU) 2018/605 of the Commission.

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Composition :

Identification	Classification (EC) 1272/2008	Note	%
INDEX: Z470 EC: 919-857-5 REACH: 01-2119463258-33 HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS	GHS07, GHS08, GHS02 Dgr Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H336 EUH066		50 $\leq$ x % < 100
INDEX: 650-002-00-6 CAS: 8006-64-2 EC: 232-350-7 REACH: 01-2119553060-53 TURPENTINE, OIL	GHS02, GHS08, GHS07, GHS09 Dgr Flam. Liq. 3, H226 Acute Tox. 4, H332 Acute Tox. 4, H312 Acute Tox. 4, H302 Asp. Tox. 1, H304 Eye Irrit. 2, H319 Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 2, H411	[i]	10 $\leq$ x % < 25
INDEX: Z365 CAS: 8002-74-2 EC: 232-315-6 REACH: 01-2119488076-30 PARAFFIN WAXES AND HYDROCARBON WAXES		[i]	2.5 $\leq$ x % < 10

Information on ingredients :

(Full text of H-phrases: see section 16)

[i] Substance for which maximum workplace exposure limits are available.

SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

4.1. description of first aid measures

In the event of exposure by inhalation :

In the event of massive inhalation, remove the person exposed to fresh air. Keep warm and at rest.

If the person is unconscious, place in recovery position. Notify a doctor in all events, to ascertain whether observation and supportive hospital

care will be necessary.

If breathing is irregular or has stopped, effect mouth-to-mouth resuscitation and call a doctor.

In the event of splashes or contact with eyes :

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

If there is any redness, pain or visual impairment, consult an ophthalmologist.

In the event of splashes or contact with skin :

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

In the event of an allergic reaction, seek medical attention.

If the contaminated area is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

In the event of swallowing :

Do not give the patient anything orally.

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.

Keep the person exposed at rest. Do not force vomiting.

Seek medical attention immediately, showing the label.

If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5 : FIREFIGHTING MEASURES

Flammable.

Chemical powders, carbon dioxide and other extinguishing gas are suitable for small fires.

5.1. Extinguishing media

Keep packages near the fire cool, to prevent pressurised containers from bursting.

Suitable methods of extinction

In the event of a fire, use :

- sprayed water or water mist
- water with AFFF (Aqueous Film Forming Foam) additive
- foam
- multipurpose ABC powder
- BC powder
- carbon dioxide (CO₂)
- halon

Prevent the effluent of fire-fighting measures from entering drains or waterways.

Unsuitable methods of extinction

In the event of a fire, do not use :

- water jet

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO₂)

5.3. Advice for firefighters

Fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

SECTION 6 : ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

For non first aid worker

Because of the organic solvents contained in the mixture, eliminate sources of ignition and ventilate the area.

Avoid inhaling the vapors.

Avoid any contact with the skin and eyes.

If a large quantity has been spilt, evacuate all personnel and only allow intervention by trained operators equipped with safety apparatus.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

If the product contaminates waterways, rivers or drains, alert the relevant authorities in accordance with statutory procedures

Use drums to dispose of collected waste in compliance with current regulations (see section 13).

6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

6.4. Reference to other sections

No data available.

SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

Individuals with a history of skin sensitisation should not, under any circumstance, handle this mixture.

7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Ensure that there is adequate ventilation, especially in confined areas.

Remove contaminated clothing and protective equipment before entering eating areas.

Fire prevention :

Handle in well-ventilated areas.

Vapours are heavier than air. They can spread along the ground and form mixtures that are explosive with air.

Prevent the formation of flammable or explosive concentrations in air and avoid vapor concentrations higher than the occupational exposure limits.

Prevent the accumulation of electrostatic charges with connections to earth.

The mixture can become electrostatically charged: always ground when decanting. Wear antistatic shoes and clothing and make floors of non-conductive

Use the mixture in premises free of naked flames or other sources of ignition and ensure that electrical equipment is suitably protected.

Keep packages tightly closed and away from sources of heat, sparks and naked flames.

Do not use tools which may produce sparks. Do not smoke.

Prevent access by unauthorised personnel.

Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Avoid inhaling vapors. Carry out any industrial operation which may give rise to this in a sealed apparatus.

Provide vapor extraction at the emission source and also general ventilation of the premises.

Also provide breathing apparatus for certain short tasks of an exceptional nature and for emergency interventions.

In all cases, recover emissions at source.

Avoid skin and eye contact with this mixture.

Packages which have been opened must be reclosed carefully and stored in an upright position.

Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

Never open the packages under pressure.

7.2. Conditions for safe storage, including any incompatibilities

No data available.

Storage

Keep out of reach of children.

Keep the container tightly closed in a dry, well-ventilated place.

Keep away from all sources of ignition - do not smoke.

Keep well away from all sources of ignition, heat and direct sunlight.

Avoid accumulation of electrostatic charges.

The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

Packaging

Always keep in packaging made of an identical material to the original.

7.3. Specific end use(s)

No data available.

SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters**Occupational exposure limits :**

- UK :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
8006-64-2	100 ppm	150 ppm	-	-	-
TURPENTINE, OIL	566 mg/m3	850 mg/m3	-	-	-
8002-74-2	2 mg/m3	6 mg/m3	-	-	-
PARAFFIN WAXES AND HYDROCARBON WAXES					

Derived no effect level (DNEL) or derived minimum effect level (DMEL):

HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS

Final use:

Exposure method:

Potential health effects:

DNEL :

Workers.

Dermal contact.

Long term systemic effects.

208 mg/kg body weight/day

Exposure method:

Potential health effects:

DNEL :

Inhalation.

Long term systemic effects.

871 mg of substance/m3

Final use:

Exposure method:

Potential health effects:

DNEL :

Consumers.

Ingestion.

Long term systemic effects.

125 mg/kg body weight/day

Exposure method:

Potential health effects:

DNEL :

Dermal contact.

Long term systemic effects.

125 mg/kg body weight/day

Exposure method:

Potential health effects:

DNEL :

Inhalation.

Long term systemic effects.

185 mg of substance/m3

8.2. Exposure controls**Personal protection measures, such as personal protective equipment**

Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE) :



Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles with protective sides accordance with standard ISO 16321.

In the event of high danger, protect the face with a face shield.

Prescription glasses are not considered as protection.

Individuals wearing contact lenses should wear prescription glasses during work where they may be exposed to irritant vapours.

Provide eyewash stations in facilities where the product is handled constantly.

- Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN ISO 374-1.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))

- PVA (Polyvinyl alcohol)

- Body protection

Avoid skin contact.

Wear suitable protective clothing.

Suitable type of protective clothing :

In the event of substantial spatter, wear liquid-tight protective clothing against chemical risks (type 3) in accordance with EN14605/A1 to prevent skin contact.

In the event of a risk of splashing, wear protective clothing against chemical risks (type 6) in accordance with EN13034/A1 to prevent skin contact.

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

- Respiratory protection

Avoid inhaling vapors.

If the ventilation is insufficient, wear appropriate breathing apparatus.

When workers are confronted with concentrations that are above occupational exposure limits, they must wear a suitable, approved, respiratory protection device.

Anti-gas and vapour filter(s) (Combined filters) in accordance with standard EN14387 :

- A1 (Brown)

SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical state

Physical state :	Paste.
------------------	--------

Colour

wood dye

Odour

Odour threshold :	Not stated.
-------------------	-------------

Melting point

Melting point/melting range :	Not relevant.
-------------------------------	---------------

Freezing point

Freezing point / Freezing range :	Not stated.
-----------------------------------	-------------

Boiling point or initial boiling point and boiling range

Boiling point/boiling range :	Not relevant.
-------------------------------	---------------

Flammability

Flammability (solid, gas) :	Not stated.
-----------------------------	-------------

Lower and upper explosion limit

Explosive properties, lower explosivity limit (%) :	Not stated.
---	-------------

Explosive properties, upper explosivity limit (%) :	Not stated.
---	-------------

Flash point

Flash Point Interval :	23°C <= FP <= 55°C
------------------------	--------------------

Auto-ignition temperature

Self-ignition temperature :	Not relevant.
-----------------------------	---------------

Decomposition temperature

Decomposition point/decomposition range :	Not relevant.
---	---------------

pH

pH (aqueous solution) :	Not stated.
-------------------------	-------------

pH :	Not relevant.
------	---------------

Kinematic viscosity

Viscosity :	Not stated.
-------------	-------------

Solubility

Water solubility :	Insoluble.
--------------------	------------

Fat solubility :	Not stated.
------------------	-------------

Partition coefficient n-octanol/water (log value)

Partition coefficient: n-octanol/water :	Not stated.
--	-------------

Vapour pressure

Vapour pressure (50°C) :	Not relevant.
--------------------------	---------------

Density and/or relative density

Density :	0.75-0.85
-----------	-----------

Relative vapour density

Vapour density :	Not stated.
------------------	-------------

Particle characteristics

The mixture does not contain nanoforms.

9.2. Other information

No data available.

9.2.1. Information with regard to physical hazard classes

No data available.

9.2.2. Other safety characteristics

No data available.

SECTION 10 : STABILITY AND REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

10.4. Conditions to avoid

Any apparatus likely to produce a flame or to have a metallic surface at high temperature (burners, electric arcs, furnaces etc.) must not be allowed on the premises.

Avoid :

- accumulation of electrostatic charges.
- heating
- heat
- flames and hot surfaces

10.5. Incompatible materials

No data available.

10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)
- carbon dioxide (CO₂)

SECTION 11 : TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

11.1.1. Substances

a) Acute toxicity :

HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS

Oral route : LD50 > 5000 mg/kg body weight
Species : Rat
OECD Guideline 401 (Acute Oral Toxicity)

Dermal route : LD50 > 5000 mg/kg body weight
Species : Rabbit
OECD Guideline 402 (Acute Dermal Toxicity)

Inhalation route (Vapours) : LC50 > 5000 mg/l
Species : Rat
OECD Guideline 403 (Acute Inhalation Toxicity)

b) Skin corrosion/skin irritation :

No data available.

c) Serious damage to eyes/eye irritation :

No data available.

d) Respiratory or skin sensitisation :

No data available.

e) Germ cell mutagenicity :

HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS

No mutagenic effect.

f) Carcinogenicity :

HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS

Carcinogenicity Test :

Negative.

No carcinogenic effect.

g) Reproductive toxicant :

No data available.

h) Specific target organ systemic toxicity - single exposure :

No data available.

i) Specific target organ systemic toxicity - repeated exposure :

No data available.

j) Aspiration hazard :

No data available.

11.1.2. Mixture

11.1.2.1 Information on hazard classes

a) Acute toxicity :

Oral route : No data available.

Dermal route : No data available.

Inhalation route (Dusts/mist) : No data available.

b) Skin corrosion/skin irritation :

May cause reversible damage to the skin; namely inflammation of the skin or the formation of erythema and eschar or oedema following exposure up to four hours.

Repeated or prolonged contact with the mixture may cause removal of natural oil from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

c) Serious damage to eyes/eye irritation :

May have reversible effects on the eyes, such as eye irritation which is totally reversible by the end of observation at 21 days.

Splashes in the eyes may cause irritation and reversible damage

d) Respiratory or skin sensitisation :

May cause an allergic reaction by skin contact.

e) Germ cell mutagenicity :

No data available.

f) Carcinogenicity :

No data available.

g) Reproductive toxicant :

No data available.

h) Specific target organ systemic toxicity - single exposure :

Narcotic effects may occur, such as drowsiness, narcosis, decreased alertness, loss of reflexes, lack of coordination or dizziness.

Effects may also occur in the form of violent headaches or nausea, judgement disorder, giddiness, irritability, fatigue or memory disturbance.

i) Specific target organ systemic toxicity - repeated exposure :

No data available.

j) Aspiration hazard :

No data available.

11.1.2.2 Other information

Symptoms related to the physical, chemical and toxicological characteristics

Exposure to vapours from solvents in the mixture in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system.

Symptoms produced will include headaches, numbness, dizziness, fatigue, muscular asthenia and, in extreme cases, loss of consciousness.

Monograph(s) from the IARC (International Agency for Research on Cancer) :

CAS 9002-88-4 : IARC Group 3 : The agent is not classifiable as to its carcinogenicity to humans.

11.2. Information on other hazards

Endocrine disrupting properties

The mixture does not contain any substance evaluated as an endocrine disruptor with effects on human health.

SECTION 12 : ECOLOGICAL INFORMATION

Harmful to aquatic life with long lasting effects.

The product must not be allowed to run into drains or waterways.

12.1. Toxicity

12.1.1. Substances

HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS

Fish toxicity : LC50 > 1000 mg/l
Species : Oncorhynchus mykiss
Duration of exposure : 96 h
OCDE Ligne directrice 203 (Poisson, essai de toxicité aiguë)

NOEC = 0.23 mg/l
Species : Oncorhynchus mykiss
Duration of exposure : 28 jours

Crustacean toxicity : EC50 > 1000 mg/l
Species : Daphnia magna
Duration of exposure : 48 h
OCDE Ligne directrice 202 (Daphnia sp., essai d'immobilisation immédiate)

NOEC = 0.13 mg/l
Species : Daphnia magna
Duration of exposure : 21 jours

Algae toxicity : ECr50 > 1000 mg/l
Species : Pseudokirchnerella subcapitata
Duration of exposure : 72 h
OCDE Ligne directrice 201 (Algues, Essai d'inhibition de la croissance)

NOEC = 3 mg/l
Species : Pseudokirchnerella subcapitata
Duration of exposure : 72 h
OCDE Ligne directrice 201 (Algues, Essai d'inhibition de la croissance)

12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

12.2. Persistence and degradability

12.2.1. Substances

HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS

Biodegradability : no degradability data is available, the substance is considered as not degrading quickly.

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Endocrine disrupting properties

The mixture does not contain any substance evaluated as an endocrine disruptor with environmental effects.

12.7. Other adverse effects

No data available.

SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air,

soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging :

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

SECTION 14 : TRANSPORT INFORMATION

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2025 - IMDG 2024 [42-24] - ICAO/IATA 2025 [66]).

14.1. UN number or ID number

3175

14.2. UN proper shipping name

UN3175=SOLIDS or mixtures of solids (such as preparations and wastes) CONTAINING FLAMMABLE LIQUID, N.O.S. having a flash-point up to 60°C

(paraffin waxes and hydrocarbon waxes)

14.3. Transport hazard class(es)

- Classification :



4.1

14.4. Packing group

II

14.5. Environmental hazards

-

14.6. Special precautions for user

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	4.1	F1	II	4.1	40	1 kg	216 274 601	E2	2	E
IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ	Stowage Handling	Segregation	
	4.1	-	II	1 kg	F-A. S-I	216 274	E2	Category B	-	
IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ	
	4.1	-	II	445	15 kg	448	50 kg	A46	E2	
	4.1	-	II	Y441	5 kg	-	-	A46	E2	

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

14.7. Maritime transport in bulk according to IMO instruments

No data available.

SECTION 15 : REGULATORY INFORMATION**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****Classification and labelling information included in section 2:**

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2023/707.

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2024/2564. (ATP 22)

Container information:

No data available.

Particular provisions :

No data available.

Restrictions applied under Title VIII of Regulation (EC) No. 1907/2006 (REACH):

The mixture does not contain any substance restricted under Annex XVII of Regulation (EC) No. 1907/2006 (REACH):

<https://echa.europa.eu/substances-restricted-under-reach>.

Authorisations agreed under Title VII of Regulation (EC) No.1907/2006 (REACH):

The mixture does not contain any substance subject to authorisation according to Annex XIV of REACH Regulation (EC) No 1907/2006:
<https://echa.europa.eu/fr/authorisation-list>.

Substances that deplete the ozone layer (EC Regulation No. 1005/2009, Montreal Protocol) :

The mixture does not contain any substance posing a risk to the ozone layer.

Persistent organic pollutants (POP) (Regulation (EU) 2019/1021):

The mixture does not contain a persistent organic pollutant.

PIC Regulation (EU) No 649/2012 concerning the export and import of hazardous chemicals (Rotterdam Convention):

The mixture is not subject to the Prior Informed Consent (PIC) procedure.

Explosives precursors :

The mixture does not contain any substance subject to Regulation (EU) 2019/1148 on the marketing and use of explosives precursors.

15.2. Chemical safety assessment

This product contains at least one substance with exposure scenarios. The RMM (risk management measures) and OC (Operating conditions) are included in the body of the SDS.

SECTION 16 : OTHER INFORMATION**Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 :**

Classification in accordance with Regulation (EC) No 1272/2008	Classification procedure
Flam. Liq. 3, H226	On basis of test data.
Skin Irrit. 2, H315	Calculation method.
Eye Irrit. 2, H319	Calculation method.
Skin Sens. 1, H317	Calculation method.
STOT SE 3, H336	Calculation method.
Aquatic Chronic 3, H412	Calculation method.

Wording of the phrases mentioned in section 3 :

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Abbreviations and acronyms :

LD50 : The dose of a test substance resulting in 50% lethality in a given time period.
LC50 : The concentration of a test substance resulting in 50% lethality in a given period.
EC50 : The effective concentration of substance that causes 50% of the maximum response.
ECr50 : The effective concentration of substance that causes 50% reduction in growth rate.
LQ : Limited Quantity
EQ : Excepted Quantity
EmS : Emergency Schedule
E : Packing Instruction
NOEC : The concentration with no observed effect.
REACH : Registration, Evaluation, Authorization and Restriction of Chemical Substances.
DNEL : Derived No-Effect Level
STEL : Short-term exposure limit
TWA : Time-Weighted Average
VLE : Threshold Limit Value (exposure)
VME : Average Exposure Value.
ADR : Agreement concerning the international carriage of dangerous goods by road.
GHS02 : Flame
GHS07 : Exclamation mark
IATA : International Air Transport Association.

IMDG : International Maritime Dangerous Goods.

ICAO : International Civil Aviation Organisation

PBT: Persistent, bioaccumulable and toxic.

PIC: Prior Informed Consent.

POP: Persistent Organic Pollutant.

RID : Regulations concerning the International carriage of Dangerous goods by rail.

SVHC : Substances of very high concern.

WGK : Water Hazard Class.

The information contained in this safety data sheet is based on our current knowledge at the time of publication and is provided in good faith. It does not constitute any guarantee of specific product properties nor establish any contractual relationship. The user remains solely responsible for safe and compliant use of the product in accordance with current regulations.
