

LIBERON - SPIRIT WOOD DYE - Light Oak - 250 mL - 014425

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P271 Use only outdoors or in a well-ventilated area.
- Precautionary statements - Disposal :
 P501 Dispose of contents/container to a waste collection center (contact the local authority)

2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) $\geq 0.1\%$ published by the European Chemicals Agency (ECHA) under article 59 of REACH: <http://echa.europa.eu/fr/candidate-list-table>

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

The mixture does not contain substances $\geq 0.1\%$ with endocrine disrupting properties in accordance with the criteria of the Delegated Regulation (EU) 2017/2100 of the Commission or Regulation (EU) 2018/605 of the Commission.

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS**3.2. Mixtures****Composition :**

Identification	Classification (EC) 1272/2008	Note	%
CAS: 67-63-0 INDEX: 603_002_00_5 CAS: 64-17-5 EC: 200-578-6 REACH: 01-2119457610-43	GHS07, GHS02 Dgr Flam. Liq. 2, H225 Eye Irrit. 2, H319	[i]	50 \leq x % < 100
CAS: 85029-59-0 INDEX: 603_064_00_3 CAS: 107-98-2 EC: 203-539-1 REACH: 01-2119457435-35 EC: 200-661-7	GHS07, GHS02 Wng Flam. Liq. 3, H226 STOT SE 3, H336	[i]	10 \leq x % < 25 0 \leq x % < 2.5
1-METHOXY-2-PROPANOL INDEX: 607_025_00_1 CAS: 123-86-4 EC: 204-658-1	GHS07, GHS02 Wng Flam. Liq. 3, H226 STOT SE 3, H336 EUH066	[i]	10 \leq x % < 25
N-BUTYL ACETATE INDEX: 603_117_00_0 REACH: 01-2119457558-25	GHS07, GHS02 Dgr Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	[i]	0 \leq x % < 2.5
PROPAN-2-OL INDEX: Z824 REACH: 01-2119485493-29 EC: 205-084-9 REACH: 01-2120763015-61	GHS09, GHS07 Skin Sens. 1B, H317 Aquatic Chronic 2, H411		
CI SOLVENT ORANGE 54			
Specific concentration limits:			
Identification	Specific concentration limits	ATE	
INDEX: 603_002_00_5 CAS: 64-17-5 EC: 200-578-6 REACH: 01-2119457610-43	inhalation: ATE = 116.9 mg/l	4h (vapours) oral: ATE = 10470 mg/kg BW	Wng
ETHANOL INDEX: 603_064_00_3 CAS: 107-98-2 EC: 203-539-1 REACH: 01-2119457435-35		inhalation: ATE = 27.596 mg/l 4h (vapours) oral: ATE = 4016 mg/kg BW	
1-METHOXY-2-PROPANOL CAS: 123-86-4 INDEX: 607_025_00_1		inhalation: ATE = 23.4 mg/l 4h (dust/mist)	

Made under licence of European Label System, Software of INFODYNE (<http://www.infodyne.fr>)

EC: 204-658-1

oral: ATE = 10760 mg/kg BW

N-BUTYL ACETATE

INDEX: 603_117_00_0

CAS: 67-63-0

EC: 200-661-7

REACH: 01-2119457558-25

dermal: ATE = 13900 mg/kg BW

oral: ATE = 5840 mg/kg BW

PROPAN-2-OL

(Full text of H-phrases: see section 16)

[i] Substance for which maximum workplace exposure limits are available.

SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

4.1. Description of first aid measures**In the event of exposure by inhalation :**

In the event of massive inhalation, remove the person exposed to fresh air. Keep warm and at rest.

If the person is unconscious, place in recovery position. Notify a doctor in all events, to ascertain whether observation and supportive hospital care will be necessary.

If breathing is irregular or has stopped, effect mouth-to-mouth resuscitation and call a doctor.

In the event of an allergic reaction, seek medical attention.

In the event of splashes or contact with eyes :

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

If there is any redness, pain or visual impairment, consult an ophthalmologist.

In the event of splashes or contact with skin :

In the event of an allergic reaction, seek medical attention.

In the event of swallowing :

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.

4.3. Description of any immediate medical attention and special treatment needed

Seek medical attention, showing the label.

If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

No data available.

SECTION 5 : FIREFIGHTING MEASURES

Flammable.

Chemical powders, carbon dioxide and other extinguishing gas are suitable for small fires.

5.1. Extinguishing media

Keep packages near the fire cool, to prevent pressurised containers from bursting.

dermal: ATE = 14112 mg/kg BW

Suitable methods of extinction

In the event of a fire, use :

Information on ingredients :

- sprayed water or water mist

- water with AFFF (Aqueous Film Forming Foam) additive

- halon

- foam

- multipurpose ABC powder

- BC powder

- carbon dioxide (CO₂)

Prevent the effluent of fire-fighting measures from entering drains or waterways.

Unsuitable methods of extinction

In the event of a fire, do not use :

- water jet

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO₂)

5.3. Advice for firefighters

Fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

SECTION 6 : ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

For non first aid worker

Because of the organic solvents contained in the mixture, eliminate sources of ignition and ventilate the area.

Avoid inhaling the vapors.

Avoid any contact with the skin and eyes.

If a large quantity has been spilt, evacuate all personnel and only allow intervention by trained operators equipped with safety apparatus.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

6.4. Reference to other sections

No data available.

SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Ensure that there is adequate ventilation, especially in confined areas.

Fire prevention :

Handle in well-ventilated areas.

Vapours are heavier than air. They can spread along the ground and form mixtures that are explosive with air.

Prevent the formation of flammable or explosive concentrations in air and avoid vapor concentrations higher than the occupational exposure limits.

Prevent the accumulation of electrostatic charges with connections to earth.

The mixture can become electrostatically charged: always ground when decanting. Wear antistatic shoes and clothing and make floors of non-conductive

Use the mixture in premises free of naked flames or other sources of ignition and ensure that electrical equipment is suitably protected.

Keep packages tightly closed and away from sources of heat, sparks and naked flames.

Do not use tools which may produce sparks. Do not smoke.

Prevent access by unauthorised personnel.

Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Avoid inhaling vapors. Carry out any industrial operation which may give rise to this in a sealed apparatus.

Provide vapor extraction at the emission source and also general ventilation of the premises.

Also provide breathing apparatus for certain short tasks of an exceptional nature and for emergency interventions.

In all cases, recover emissions at source.

Avoid eye contact with this mixture.

Packages which have been opened must be reclosed carefully and stored in an upright position.

Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

7.2. Conditions for safe storage, including any incompatibilities

No data available.

Storage

Keep out of reach of children.
 Keep the container tightly closed in a dry, well-ventilated place.
 Keep away from all sources of ignition - do not smoke.
 Keep well away from all sources of ignition, heat and direct sunlight.
 Avoid accumulation of electrostatic charges.
 The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

Packaging

Always keep in packaging made of an identical material to the original.

7.3. Specific end use(s)

No data available.

SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Occupational exposure limits :

- European Union :

CAS	VME-mg/m3 :	VME-ppm :	VLE-mg/m3 :	VLE-ppm :	Notes :
107-98-2	375	100	568	150	Peau
123-86-4		50	723	150	-

- UK :

CAS	TWA :	STEL :	Ceiling :	Criteria :
64-17-5	1000 ppm 1920 mg/m3	-	-	-
107-98-2	100 ppm 375 mg/m3	150 ppm 560 mg/m3	-	Sk
123-36-4	150 ppm 724 mg/m3	200 ppm	-	-
67-63-0	400 ppm 999 mg/m3	1250 mg/m3	-	-

966 mg/m3

Derived no effect level (DNEL) or derived minimum effect level (DMEL):

PROPAN-2-OL (CAS: 67-63-0)

Final use:

Exposure method:

Potential health effects:

DNEL :

Exposure method:

Potential health effects:

DNEL :

Final use:

Exposure method:

Potential health effects:

DNEL :

Exposure method:

Potential health effects:

DNEL :

Exposure method:

Potential health effects:

DNEL :

N-BUTYL ACETATE (CAS: 123-86-4)

Final use:

Exposure method:

Potential health effects:

DNEL :

Exposure method:

Potential health effects:

Workers.

Dermal contact:

Long term systemic effects:

888 mg/kg body weight/day

Inhalation:

Long term systemic effects:

500 mg of substance/m3

Consumers.

Ingestion.

Long term systemic effects.

26 mg/kg body weight/day

Dermal contact.

Long term systemic effects.

319 mg/kg body weight/day

Inhalation.

Long term systemic effects.

89 mg of substance/m3

Workers.

Inhalation.

Long term systemic effects.

480 mg of substance/m3

Short term local effects.

DNEL : 960 mg of substance/m³

Final use: **Consumers.**
 Exposure method: Inhalation.
 Potential health effects: Long term systemic effects.
 DNEL : 102 mg of substance/m³

1-METHOXY-2-PROPANOL (CAS: 107-98-2)

Final use: **Workers.**
 Exposure method: Dermal contact.
 Potential health effects: Long term systemic effects.
 DNEL : 50.6 mg/kg body weight/day

Exposure method: Inhalation.
 Potential health effects: Short term local effects.
 DNEL : 553.5 mg of substance/m³

Exposure method: Inhalation.
 Potential health effects:
 DNEL : 369 mg of substance/m³

ETHANOL (CAS: 64-17-5)

Final use: **Consumers.**
 Exposure method: Ingestion.
 Potential health effects: Long term systemic effects.
 DNEL : 3.3 mg/kg body weight/day

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH)
 Exposure method: Dermal contact.
 Potential health effects: Long term systemic effects.
 DNEL : 18.1 mg/kg body weight/day

Exposure method: Inhalation.
 Potential health effects: Long term systemic effects.
 DNEL : 43.9 mg of substance/m³

Final use: **Workers.**
 Exposure method: Dermal contact.
 Potential health effects: Long term systemic effects.
 DNEL : 343 mg/kg body weight/day

Exposure method: Inhalation.
 Potential health effects: Long term systemic effects.
 DNEL : 950 mg of substance/m³

Final use: **Consumers.**
 Exposure method: Ingestion.
 Potential health effects: Long term systemic effects.
 DNEL : 87 mg/kg body weight/day

Exposure method: Dermal contact.
 Potential health effects: Long term systemic effects.
 DNEL : 206 mg/kg body weight/day

Exposure method: Inhalation.
 Potential health effects: Long term systemic effects.
 DNEL : 950 mg of substance/m³

Exposure method: Inhalation.
 Potential health effects: Long term systemic effects.
 DNEL : 114 mg of substance/m³

Predicted no effect concentration (PNEC):

1-METHOXY-2-PROPANOL (CAS: 107-98-2)

Environmental compartment:	Soil.
PNEC :	2.47 mg/kg
Environmental compartment:	Fresh water.
PNEC :	10 mg/l
Environmental compartment:	Sea water.
PNEC :	100 mg/l
PNEC :	Fresh water sediment. 41.6 mg/kg
Environmental compartment:	Marine sediment.
PNEC :	4.17 mg/kg
Environmental compartment:	Waste water treatment plant.
PNEC :	100 mg/l
ETHANOL (CAS: 64-17-5)	
Environmental compartment:	Fresh water.
PNEC :	0.96 mg/l
Environmental compartment:	Sea water.
PNEC :	0.79 mg/l
Environmental compartment:	Fresh water sediment.
PNEC :	3.6 mg/kg
Environmental compartment:	Marine sediment.
PNEC :	0.63 mg/kg

8.2. Exposure controls

Personal protection measures, such as personal protective equipment

Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE) :



Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles with protective sides accordance with standard ISO 16321.

In the event of high danger, protect the face with a face shield.

Prescription glasses are not considered as protection.

Individuals wearing contact lenses should wear prescription glasses during work where they may be exposed to irritant vapours.

Provide eyewash stations in facilities where the product is handled constantly.

- Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN ISO 374-1.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- PVA (Polyvinyl alcohol)

- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))

- Body protection

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

- Respiratory protection

Avoid inhaling vapors.

If the ventilation is insufficient, wear appropriate breathing apparatus.

When workers are confronted with concentrations that are above occupational exposure limits, they must wear a suitable, approved, respiratory protection device.

Anti-gas and vapour filter(s) (Combined filters) in accordance with standard EN14387 :

- A1 (Brown)

SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES**9.1. Information on basic physical and chemical properties****Physical state**

Physical state :	Fluid liquid.
------------------	---------------

Colour

several colors possible

Odour

Odour threshold :	Not stated.
-------------------	-------------

Melting point

Melting point/melting range :	Not relevant.
-------------------------------	---------------

Freezing point

Freezing point / Freezing range :	Not stated.
-----------------------------------	-------------

Boiling point or initial boiling point and boiling range

Boiling point/boiling range :	> 35°C
-------------------------------	--------

Flammability

Flammability (solid, gas) :	Not stated.
-----------------------------	-------------

Lower and upper explosion limit

Explosive properties, lower explosivity limit (%) :	Not stated.
---	-------------

Explosive properties, upper explosivity limit (%) :	Not stated.
---	-------------

Flash point

Flash Point :	12.00 °C.
---------------	-----------

Auto-ignition temperature

Self-ignition temperature :	Not relevant.
-----------------------------	---------------

Decomposition temperature

Decomposition point/decomposition range :	Not relevant.
---	---------------

pH

pH (aqueous solution) :	Not stated.
-------------------------	-------------

pH :	Not relevant.
------	---------------

Kinematic viscosity

Viscosity :	Not stated.
-------------	-------------

Density and/or relative density**Solubility**

Water solubility :	Insoluble.
--------------------	------------

Fat solubility :	Not stated.
------------------	-------------

Partition coefficient n-octanol/water (log value)

Partition coefficient: n-octanol/water :	Not stated.
--	-------------

Vapour pressure

Vapour pressure (50°C) :	Below 110 kPa (1.10 bar).
--------------------------	---------------------------

Density :	0.8-0.9
-----------	---------

Relative vapour density

Vapour density :	Not stated.
------------------	-------------

9.2. Other information

No data available.

9.2.1. Information with regard to physical hazard classes

No data available.

9.2.2. Other safety characteristics

No data available.

SECTION 10 : STABILITY AND REACTIVITY**10.1. Reactivity**

No data available.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

10.4. Conditions to avoid

Any apparatus likely to produce a flame or to have a metallic surface at high temperature (burners, electric arcs, furnaces etc.) must not be allowed on the premises.

Avoid :

- accumulation of electrostatic charges.
- heating
- heat

10.5. Incompatible materials

No data available.

10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)
- carbon dioxide (CO₂)

SECTION 11 : TOXICOLOGICAL INFORMATION**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**

Exposure to vapours from solvents in the mixture in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system.

Symptoms produced will include headaches, numbness, dizziness, fatigue, muscular asthenia and, in extreme cases, loss of consciousness.

Repeated or prolonged contact with the mixture may cause removal of natural oil from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

May have reversible effects on the eyes, such as eye irritation which is totally reversible by the end of observation at 21 days.

Splashes in the eyes may cause irritation and reversible damage

Narcotic effects may occur, such as drowsiness, narcosis, decreased alertness, loss of reflexes, lack of coordination or dizziness. Effects may also occur in the form of violent headaches or nausea, judgement disorder, giddiness, irritability, fatigue or memory disturbance.

11.1.1. Substances**a) Acute toxicity :**

CI SOLVENT ORANGE 54 (CAS: 85029-59-0)

Oral route : LD50 > 5000 mg/kg body weight
Species : Rat
OECD Guideline 401 (Acute Oral Toxicity)

PROPAN-2-OL (CAS: 67-63-0)

Oral route : LD50 = 5840 mg/kg body weight
Species : Rat
OECD Guideline 401 (Acute Oral Toxicity)

Dermal route :

LD50 = 13900 mg/kg body weight
Species : Rabbit
OECD Guideline 402 (Acute Dermal Toxicity)

N-BUTYL ACETATE (CAS: 123-86-4)

Oral route : LD50 = 10760 mg/kg body weight
Species : Rat
OECD Guideline 423 (Acute Oral toxicity Acute Toxic Class Method)

Dermal route :

LD50 = 14112 mg/kg body weight
Species : Rabbit
OECD Guideline 402 (Acute Dermal Toxicity)

Inhalation route (Dusts/mist) :

LC50 = 23.4 mg/l

Species : Rat
 OECD Guideline 403 (Acute Inhalation Toxicity)
 Duration of exposure : 4 h

1-METHOXY-2-PROPANOL (CAS: 107-98-2)

Oral route : LD50 = 4016 mg/kg body weight
 Species : Rat

Dermal route : LD50 > 2000 mg/kg body weight
 Species : Rabbit

Inhalation route (Vapours) : LC50 = 27.596 mg/l
 Species : Rat
 Duration of exposure : 4 h

ETHANOL (CAS: 64-17-5)

Oral route : LD50 = 10470 mg/kg body weight
 Species : Rat
 OECD Guideline 401 (Acute Oral Toxicity)

Inhalation route (Vapours) : LC50 = 116.9 mg/l
 Species : Rat
 OECD Guideline 403 (Acute Inhalation Toxicity)
 Duration of exposure : 4 h

b) Skin corrosion/skin irritation :

ETHANOL (CAS: 64-17-5)

Species : Rabbit
 OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

c) Serious damage to eyes/eye irritation :

ETHANOL (CAS: 64-17-5)
 Causes serious eye irritation.
 Corneal haze :

1 <= Average score < 2 and effects totally reversible within 21 days of observation

d) Respiratory or skin sensitisation :

No data available.

e) Germ cell mutagenicity :

No data available.

f) Carcinogenicity :

No data available.

g) Reproductive toxicant :

No data available.

h) Specific target organ systemic toxicity - single exposure :

No data available.

i) Specific target organ systemic toxicity - repeated exposure :

No data available.

j) Aspiration hazard :

No data available.

11.1.2. Mixture

a) Acute toxicity :

No data available.

b) Skin corrosion/skin irritation :

No data available.

c) Serious damage to eyes/eye irritation :

No data available.

d) Respiratory or skin sensitisation :

Contains at least one sensitising substance. May cause an allergic reaction.

e) Germ cell mutagenicity :

No data available.

f) Carcinogenicity :

No data available.

g) Reproductive toxicant :

No data available.

h) Specific target organ systemic toxicity - single exposure :

No data available.

i) Specific target organ systemic toxicity - repeated exposure :

No data available.

j) Aspiration hazard :

No data available.

11.1.2.2 Other information

11.2. Information on other hazards

Monograph(s) from the IARC (International Agency for Research on Cancer) :

CAS 67-63-0 : IARC Group 3 : The agent is not classifiable as to its carcinogenicity to humans.

CAS 64-17-5 : IARC Group 1 : The agent is carcinogenic to humans.

SECTION 12 ENVIRONMENTAL INFORMATION

12.1. Toxicity

12.1.1. Substances

Crustacean toxicity : EC50 = 5.04 mg/l
Species : Daphnia magna Duration of exposure : 72 h ECr50 > 10 mg/l
Duration of exposure : 48 h
OCDE Ligne directrice 202 (Daphnia sp., essai d'immobilisation immédiate)

Aquatic plant toxicity :
Species : Lemna gibba
OCDE Ligne directrice 221 (Lemna sp. Essais d'inhibition de la croissance)

PROPAN-2-OL (CAS: 67-63-0)
Fish toxicity : LC50 > 100 mg/l
Duration of exposure : 96 h

Crustacean toxicity : EC50 > 100 mg/l
Duration of exposure : 48 h

Algae toxicity : ECr50 > 100 mg/l
Algae toxicity :

N-BUTYL ACETATE (CAS: 123-86-4)
Fish toxicity : LC50 = 18 mg/l
Species : Pimephales promelas
Duration of exposure : 96 h
OCDE Ligne directrice 203 (Poisson, essai de toxicité aiguë)

Crustacean toxicity : EC50 = 44 mg/l
Species : Daphnia magna
Duration of exposure : 48 h

Algae toxicity : ECr50 = 647.7 mg/l
Species : Desmodesmus subspicatus
Duration of exposure : 72 h
OCDE Ligne directrice 201 (Algues, Essai d'inhibition de la croissance)

1-METHOXY-2-PROPANOL (CAS: 107-98-2)
Fish toxicity : LC50 >= 1000 mg/l
Species : Oncorhynchus mykiss

	Duration of exposure : 96 h
Crustacean toxicity :	EC50 = 23300 mg/l Species : Daphnia magna Duration of exposure : 48 h
Algae toxicity :	ECr50 > 1000 mg/l Species : Pseudokirchnerella subcapitata
ETHANOL (CAS: 64-17-5) Fish toxicity :	Species : Leuciscus idus melanotus Duration of exposure : 48 h OCDE Ligne directrice 203 (Poisson, essai de toxicité aiguë)
Crustacean toxicity :	EC50 > 100 mg/l Species : Daphnia magna Duration of exposure : 24 h OCDE Ligne directrice 202 (Daphnia sp., essai d'immobilisation immédiate)
Algae toxicity :	ECr50 > 5000 mg/l Species : Chlorella pyrenoidosa Duration of exposure : 72 h OCDE Ligne directrice 201 (Algues, Essai d'inhibition de la croissance)

No aquatic toxicity data available for the mixture.

12.1.2. Mixtures

log K_{ow} < 3.

12.2. Persistence and degradability

12.2.1. Substances

CI SOLVENT ORANGE 54 (CAS: 85029-59-0)

Biodegradability :

Non-rapidly degradable.

PROPAN-2-OL (CAS: 67-63-0)

Biodegradability :

Rapidly degradable.

N-BUTYL ACETATE (CAS: 123-86-4)

Biodegradability :

Rapidly degradable.

1-METHOXY-2-PROPANOL (CAS: 107-98-2)

Biodegradability :

Rapidly degradable.

ETHANOL (CAS: 64-17-5)

Biodegradability :

Octanol/water partition coefficient :

BCF < 100

12.3. Bioaccumulative potential

12.3.1. Substances

1-METHOXY-2-PROPANOL (CAS: 107-98-2)

Bioaccumulation :

No data available.

No data available.

12.6. Endocrine disrupting properties

No data available.

No data available.

SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging :

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

SECTION 14 : TRANSPORT INFORMATION

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2023 - IMDG 2022 [41-22] - ICAO/IATA 2024 [65]).

14.1. UN number or ID number

1263

14.2. UN proper shipping name

UN1263=PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning and reducing compound)

14.3. Transport hazard class(es)

- Classification :



3

14.4. Packing group

II

14.5. Environmental hazards

-

14.6. Special precautions for user

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	3	F1	II	3	33	5 L	163 367 640D 650	E2	2	D/E
Provis	MDG	Class	2°Label	Pack gr.	LQ	EMS	EQ	Stowage Handling	Segregati	
	3	-	II	5 L	F-E S-E	163 367	E2	Category B	-	
IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ	
For excepted quantities, see part 2.6 of the OACI/IATA 358 chapter 3.5 of the ADR 364 and IMDG.							60 L	A3 A72	E2	
			II	Y341	1 L	-	-	A3 A72 A192	E2	

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

14.7. Maritime transport in bulk according to IMO instruments

No data available.

SECTION 15 : REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Classification and labelling information included in section 2:

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2022/692 (ATP 18)

Container information:

Containers to be fitted with a tactile warning of danger (see EC Regulation No. 1272/2008, Annex II, Part 3).

The mixture does not contain any substance restricted under Annex XVII of Regulation (EC) No. 1907/2006 (REACH):

<https://echa.europa.eu/substances-restricted-under-reach>.

Particular provisions :

No data available.

Persistent organic pollutants (POP) (Regulation (EU) 2019/1021):

15.2. Chemical safety assessment

This product contains at least one substance with exposure scenarios. The RMM (risk management measures) and OC (Operating conditions) are included in the body of the SDS.

SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

Wording of the phrases mentioned in section 3 :

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Abbreviations and acronyms :

LD50 : The dose of a test substance resulting in 50% lethality in a given time period.

LC50 : The concentration of a test substance resulting in 50% lethality in a given period.

EC50 : The effective concentration of substance that causes 50% of the maximum response.

ECr50 : The effective concentration of substance that causes 50% reduction in growth rate.

REACH : Registration, Evaluation, Authorization and Restriction of Chemical Substances.

BW : Body Weight

DNEL : Derived No-Effect Level

PNEC : Predicted No-Effect Concentration

STEL : Short-term exposure limit

TWA : Time Weighted Averages

TLV : Threshold Limit Value (exposure)

AEV : Average Exposure Value.

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefahrdungsklasse (Water Hazard Class).

GHS02 : Flame

GHS07 : Exclamation mark

PBT: Persistent, bioaccumulable and toxic.

vPvB : Very persistent, very bioaccumulable.

SVHC : Substances of very high concern.

ATE : Acute Toxicity Estimate