

MOTO WASH 1LX12 IPONE REF 800670 - A18410



SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2015/830)

SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name : MOTO WASH 1LX12 IPONE REF 800670

Product code : A18410.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Detergent

1.3. Details of the supplier of the safety data sheet

Registered company name : IPONE.

Address : La Meunière .13480.CABRIES .FRANCE.

Telephone : +33 (0)4 42 94 05 65. Fax : +33 (0)4 42 94 05 66.

info@ipone.fr

1.4. Emergency telephone number : +33 (0)1 45 42 59 59.

Association/Organisation : INRS / ORFILA <http://www.centres-antipoison.net>.

SECTION 2 : HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

Skin corrosion, Category 1C (Skin Corr. 1C, H314).

Serious eye damage, Category 1 (Eye Dam. 1, H318).

This mixture does not present a physical hazard. Refer to the recommendations regarding the other products present on the site.

This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

2.2. Label elements

Detergent mixture (see section 15).

Mixture for spray application.

In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms :



GHS05

Signal Word :

DANGER

Product identifiers :

014-010-00-8 DISODIUM METASILICATE

Hazard statements :

H314 Causes severe skin burns and eye damage.

Precautionary statements - General :

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

Precautionary statements - Prevention :

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary statements - Response :

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor/...

Precautionary statements - Disposal :

P501 Dispose of contents/container according to the local rules.

**MOTO WASH 1LX12 IPONE REF 800670 - A18410**

**2.3. Other hazards**

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC)  $\geq 0.1\%$  published by the European Chemicals Agency (ECHA) under article 57 of REACH: <http://echa.europa.eu/fr/candidate-list-table>

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

**SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS**

**3.2. Mixtures**

**Composition :**

Identification	(EC) 1272/2008	Note	%
INDEX: I34590_94_8 CAS: 34590-94-8 EC: 252-104-2 REACH: 01-2119450011-60  DIPROPYLENE GLYCOL MONOMETHYL ETHER		[1]	2.5 $\leq$ x % < 10
INDEX: 603-064-00-3 CAS: 107-98-2 EC: 203-539-1 REACH: 01-2119457435-35  1-METHOXY-2-PROPANOL	GHS02, GHS07 Wng Flam. Liq. 3, H226 STOT SE 3, H336	[1]	2.5 $\leq$ x % < 10
INDEX: A04272/01 CAS: 68439-51-0  LAURYLMYRISTYL POLYGLYCOL ETHER	Aquatic Chronic 3, H412		0 $\leq$ x % < 2.5
INDEX: 68891_383A CAS: 68891-38-3 EC: 500-234-8 REACH: 01-2119488639-16  TA-A / ALCOHOLS, C12-14, ETHOXYLATED, SULFATES, SODIUM SALTS	GHS05 Dgr Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Chronic 3, H412		0 $\leq$ x % < 2.5
INDEX: 014-010-00-8 CAS: 6834-92-0 EC: 229-912-9 REACH: 01-2119449811-37  DISODIUM METASILICATE	GHS05, GHS07 Dgr Skin Corr. 1B, H314 STOT SE 3, H335		0 $\leq$ x % < 2.5

(Full text of H-phrases: see section 16)

**Information on ingredients :**

Substances may not have a REACH Registration No.. because they are manufactured / imported in quantities less than 1 ton / year, or they are complex substances or they are exempted from registration under REACH.

[1] Substance for which maximum workplace exposure limits are available.

**SECTION 4 : FIRST AID MEASURES**

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

**4.1. Description of first aid measures**

**In the event of exposure by inhalation :**

Consult doctor if symptoms develop.

**In the event of splashes or contact with eyes :**

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

Regardless of the initial state, refer the patient to an ophthalmologist and show him the label.

**In the event of splashes or contact with skin :**

Remove any soiled or splashed clothing immediately.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

If the contaminated area is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

**MOTO WASH 1LX12 IPONE REF 800670 - A18410**

---

**In the event of swallowing :**

Do not give the patient anything orally.  
Seek medical attention immediately, showing the label.

**4.2. Most important symptoms and effects, both acute and delayed**

No data available.

**4.3. Indication of any immediate medical attention and special treatment needed**

**Specific and immediate treatment :**

No data available.

**Information for the doctor :**

No data available.

---

**SECTION 5 : FIREFIGHTING MEASURES**

Non-flammable.

**5.1. Extinguishing media**

**Suitable methods of extinction**

Non-flammable

**Unsuitable methods of extinction**

In the event of a fire, do not use :

Not known

**5.2. Special hazards arising from the substance or mixture**

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)

- carbon dioxide (CO<sub>2</sub>)

**5.3. Advice for firefighters**

Due to the toxicity of the gas emitted on thermal decomposition of the products, fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

---

**SECTION 6 : ACCIDENTAL RELEASE MEASURES**

**6.1. Personal precautions, protective equipment and emergency procedures**

Consult the safety measures listed under headings 7 and 8.

**For non first aid worker**

Avoid any contact with the skin and eyes.

**For first aid worker**

First aid workers will be equipped with suitable personal protective equipment (See section 8).

**6.2. Environmental precautions**

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

**6.3. Methods and material for containment and cleaning up**

Neutralise with an acidic decontaminant.

If the ground is contaminated, once the product has been recovered by sponging with an inert and non-combustible absorbent material, wash the contaminated area in plenty of water.

Clean preferably with a detergent, do not use solvents.

**6.4. Reference to other sections**

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

See Section 7 for information on safe handling.

**MOTO WASH 1LX12 IPONE REF 800670 - A18410**

**SECTION 7 : HANDLING AND STORAGE**

Requirements relating to storage premises apply to all facilities where the mixture is handled.

**7.1. Precautions for safe handling**

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Emergency showers and eye wash stations will be required in facilities where the mixture is handled constantly.

**Fire prevention :**

Prevent access by unauthorised personnel.

**Recommended equipment and procedures :**

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

**Prohibited equipment and procedures :**

No smoking, eating or drinking in areas where the mixture is used.

**7.2. Conditions for safe storage, including any incompatibilities**

Store receptacle in a well ventilated area.

Store in cool, dry conditions in well sealed receptacles.

**Storage**

Keep out of reach of children.

**Packaging**

Always keep in packaging made of an identical material to the original.

**7.3. Specific end use(s)**

No data available.

**SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION**

**8.1. Control parameters**

**Occupational exposure limits :**

- European Union (2017/2398, 2017/164, 2009/161, 2006/15/CE, 2000/39/CE, 98/24/CE) :

CAS	VME-mg/m <sup>3</sup> :	VME-ppm :	VLE-mg/m <sup>3</sup> :	VLE-ppm :	Notes :
34590-94-8	308	50	-	-	Peau
107-98-2	375	100	568	150	Peau

- ACGIH TLV (American Conference of Governmental Industrial Hygienists, Threshold Limit Values, 2010) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
34590-94-8	100 ppm	150 ppm		Skin	
107-98-2	100 ppm	150 ppm			

- Germany - AGW (BAuA - TRGS 900, 29/01/2018) :

CAS	VME :	VME :	Excess	Notes
34590-94-8		50 ppm 310 mg/m <sup>3</sup>		1(I)
107-98-2		100 ppm 370 mg/m <sup>3</sup>		2(I)

- France (INRS - ED984 :2016) :

CAS	VME-ppm :	VME-mg/m <sup>3</sup> :	VLE-ppm :	VLE-mg/m <sup>3</sup> :	Notes :	TMP No :
34590-94-8	50	308	-	-	*	84
107-98-2	50	188	100	375	*	84

- UK / WEL (Workplace exposure limits, EH40/2005, 2011) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
34590-94-8	50 ppm 308 mg/m <sup>3</sup>	- ppm - mg/m <sup>3</sup>		Sk	
107-98-2	100 ppm 375 mg/m <sup>3</sup>	150 ppm 560 mg/m <sup>3</sup>		Sk	

**Derived no effect level (DNEL) or derived minimum effect level (DMEL):**

TA-A / ALCOHOLS, C12-14, ETHOXYLATED, SULFATES, SODIUM SALTS (CAS: 68891-38-3)

**MOTO WASH 1LX12 IPONE REF 800670 - A18410**

**Final use:**

Exposure method:  
Potential health effects:  
DNEL :

**Workers.**

Dermal contact.  
Long term systemic effects.  
2750 mg/kg body weight/day

Exposure method:  
Potential health effects:  
DNEL :

Dermal contact.  
Long term local effects.  
132 µg of substance/cm<sup>2</sup>

Exposure method:  
Potential health effects:  
DNEL :

Inhalation.  
Long term systemic effects.  
175 mg of substance/m<sup>3</sup>

**Final use:**

Exposure method:  
Potential health effects:  
DNEL :

**Consumers.**

Ingestion.  
Long term systemic effects.  
15 mg/kg body weight/day

Exposure method:  
Potential health effects:  
DNEL :

Dermal contact.  
Long term systemic effects.  
1650 mg/kg body weight/day

Exposure method:  
Potential health effects:  
DNEL :

Dermal contact.  
Long term local effects.  
79 µg of substance/cm<sup>2</sup>

Exposure method:  
Potential health effects:  
DNEL :

Inhalation.  
Long term systemic effects.  
52 mg of substance/m<sup>3</sup>

1-METHOXY-2-PROPANOL (CAS: 107-98-2)

**Final use:**

Exposure method:  
Potential health effects:  
DNEL :

**Workers.**

Dermal contact.  
Long term systemic effects.  
183 mg/kg body weight/day

Exposure method:  
Potential health effects:  
DNEL :

Inhalation.  
Long term systemic effects.  
269 mg of substance/m<sup>3</sup>

Exposure method:  
Potential health effects:  
DNEL :

Inhalation.  
Short term systemic effects.  
553.5 mg of substance/m<sup>3</sup>

Exposure method:  
Potential health effects:  
DNEL :

Inhalation.  
Short term local effects.  
553.5 mg of substance/m<sup>3</sup>

**Final use:**

Exposure method:  
Potential health effects:  
DNEL :

**Consumers.**

Dermal contact.  
Long term systemic effects.  
78 mg/kg body weight/day

Exposure method:  
Potential health effects:  
DNEL :

Inhalation.  
Long term systemic effects.  
43.9 mg of substance/m<sup>3</sup>

DIPROPYLENE GLYCOL MONOMETHYL ETHER (CAS: 34590-94-8)

**MOTO WASH 1LX12 IPONE REF 800670 - A18410**

**Final use:**

Exposure method:  
Potential health effects:  
DNEL :

**Workers.**

Dermal contact.  
Long term systemic effects.  
283 mg/kg body weight/day

Exposure method:  
Potential health effects:  
DNEL :

Inhalation.  
Long term systemic effects.  
308 mg of substance/m<sup>3</sup>

**Final use:**

Exposure method:  
Potential health effects:  
DNEL :

**Consumers.**

Ingestion.  
Long term systemic effects.  
36 mg/kg body weight/day

Exposure method:  
Potential health effects:  
DNEL :

Dermal contact.  
Long term systemic effects.  
121 mg/kg body weight/day

Exposure method:  
Potential health effects:  
DNEL :

Inhalation.  
Long term systemic effects.  
37.2 mg of substance/m<sup>3</sup>

**Predicted no effect concentration (PNEC):**

TA-A / ALCOHOLS, C12-14, ETHOXYLATED, SULFATES, SODIUM SALTS (CAS: 68891-38-3)

Environmental compartment:  
PNEC : Soil.  
7.5 mg/kg

Environmental compartment:  
PNEC : Fresh water.  
0.24 mg/l

Environmental compartment:  
PNEC : Sea water.  
0.024 mg/l

Environmental compartment:  
PNEC : Intermittent waste water.  
0.071 mg/l

Environmental compartment:  
PNEC : Fresh water sediment.  
0.917 mg/kg

Environmental compartment:  
PNEC : Marine sediment.  
0.092 mg/kg

Environmental compartment:  
PNEC : Waste water treatment plant.  
10 g/l

1-METHOXY-2-PROPANOL (CAS: 107-98-2)

Environmental compartment:  
PNEC : Soil.  
4.59 mg/kg

Environmental compartment:  
PNEC : Fresh water.  
10 mg/l

Environmental compartment:  
PNEC : Sea water.  
1 mg/l

Environmental compartment:  
PNEC : Intermittent waste water.  
100 mg/l

Environmental compartment:  
Fresh water sediment.

**MOTO WASH 1LX12 IPONE REF 800670 - A18410**

PNEC :	52.3 mg/kg
Environmental compartment: PNEC :	Marine sediment. 5.2 mg/kg
Environmental compartment: PNEC :	Waste water treatment plant. 100 mg/l
<b>DIPROPYLENE GLYCOL MONOMETHYL ETHER (CAS: 34590-94-8)</b>	
Environmental compartment: PNEC :	Soil. 2.74 mg/kg
Environmental compartment: PNEC :	Fresh water. 19 mg/l
Environmental compartment: PNEC :	Sea water. 1.9 mg/l
Environmental compartment: PNEC :	Intermittent waste water. 190 mg/l
Environmental compartment: PNEC :	Fresh water sediment. 70.2 mg/kg
Environmental compartment: PNEC :	Marine sediment. 7.02 mg/kg
Environmental compartment: PNEC :	Waste water treatment plant. 4168 mg/l

## 8.2. Exposure controls

### Personal protection measures, such as personal protective equipment

Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

### - Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles with protective sides accordance with standard EN166.

In the event of high danger, protect the face with a face shield.

When spraying, wear a face shield in accordance with standard EN166.

Prescription glasses are not considered as protection.

Individuals wearing contact lenses should wear prescription glasses during work where they may be exposed to irritant vapours.

Provide eyewash stations in facilities where the product is handled constantly.

### - Hand protection

Wear suitable protective gloves in the event of prolonged or repeated skin contact.

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN374.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- Natural latex

- PVC (polyvinyl chloride)

Let the glove manufacturer advise you on the choice of gloves and their duration of use for your operating conditions

Recommended properties :

- Impervious gloves in accordance with standard EN374

**MOTO WASH 1LX12 IPONE REF 800670 - A18410**

**- Body protection**

Avoid skin contact.

Wear suitable protective clothing.

Suitable type of protective clothing :

Wear suitable protective clothing and, in particular, an apron and boots. These items of clothing shall be maintained in good condition and cleaned after use.

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

**- Respiratory protection**

Anti-gas and vapour filter(s) (Combined filters) in accordance with standard EN14387 :

- A1 (Brown)

Types, classes and filters for respiratory protection above are recommended in case of confrontation at concentrations higher than the exposure limits specified under 8.1. (Control parameters) .They should be adjusted according to actual conditions. they may not be necessary if the product is used outdoors or in a well ventilated area.

---

**SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES**

**9.1. Information on basic physical and chemical properties**

**General information :**

Physical state : Fluid liquid.

**Important health, safety and environmental information**

pH : Not stated.  
Strongly basic.

Boiling point/boiling range : Not specified.

Flash Point Interval : 60°C < FP <= 93°C

Vapour pressure (50°C) : Below 110 kPa (1.10 bar).

Density : > 1

Water solubility : Dilutable.

Melting point/melting range : Not specified.

Self-ignition temperature : Not specified.

Decomposition point/decomposition range : Not specified.

**9.2. Other information**

No data available.

---

**SECTION 10 : STABILITY AND REACTIVITY**

**10.1. Reactivity**

No data available.

**10.2. Chemical stability**

This mixture is stable under the recommended handling and storage conditions in section 7.

**10.3. Possibility of hazardous reactions**

No data available.

**10.4. Conditions to avoid**

Avoid :

- frost

To be translated (XML)

**10.5. Incompatible materials**

No incompatible materials known.

**10.6. Hazardous decomposition products**

The thermal decomposition may release/form :

- carbon monoxide (CO)

- carbon dioxide (CO<sub>2</sub>)



**MOTO WASH 1LX12 IPONE REF 800670 - A18410**

**SECTION 11 : TOXICOLOGICAL INFORMATION**

**11.1. Information on toxicological effects**

May cause irreversible damage to the skin; namely, visible necrosis through the epidermis and into the dermis, following exposure between one and four hours.

Corrosive reactions are typified by ulcers, bleeding, bloody scabs, and, by the end of observation at 14 days, by discolouration due to blanching of the skin, complete areas of alopecia, and scars.

**11.1.1. Substances**

No toxicological data available for the substances.

**11.1.2. Mixture**

**Skin corrosion/skin irritation :**

The 'corrosive' classification is based on the low/high pH which has been confirmed by tests.

Causes severe skin burns and eye damage.

**Serious damage to eyes/eye irritation :**

Corrosive classification is based on an extreme pH value.

Causes serious eye irritation.

**Respiratory or skin sensitisation :**

To be translated (XML)

**Germ cell mutagenicity :**

Based on available data; the classification criteria are not met.

**Carcinogenicity :**

Based on available data; the classification criteria are not met.

**Reproductive toxicant :**

Based on available data; the classification criteria are not met.

**Specific target organ systemic toxicity - single exposure :**

Based on available data; the classification criteria are not met.

**Specific target organ systemic toxicity - repeated exposure :**

Based on available data; the classification criteria are not met.

**Aspiration hazard :**

Based on available data; the classification criteria are not met.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

No further relevant information available.

**Other information**

No further relevant information available.

**Monograph(s) from the IARC (International Agency for Research on Cancer) :**

CAS 140-11-4 : IARC Group 3 : The agent is not classifiable as to its carcinogenicity to humans.

**SECTION 12 : ECOLOGICAL INFORMATION**

**12.1. Toxicity**

**12.1.1. Substances**

TA-A / ALCOHOLS, C12-14, ETHOXYLATED, SULFATES, SODIUM SALTS (CAS: 68891-38-3)

Fish toxicity : ECx > 1 mg/l

Crustacean toxicity : 0,1 < NOEC <= 1 mg/l

LAURYLMYRISTYL POLYGLYCOL ETHER (CAS: 68439-51-0)

Fish toxicity : EC50 mg/l  
Species : Leuciscus idus  
Other guideline

Crustacean toxicity : EC50 mg/l  
Species : Daphnia magna  
OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

**MOTO WASH 1LX12 IPONE REF 800670 - A18410**

Aquatic plant toxicity : EC10 mg/l

**12.1.2. Mixtures**

No aquatic toxicity data available for the mixture.

**12.2. Persistence and degradability**

**12.2.1. Substances**

TA-A / ALCOHOLS, C12-14, ETHOXYLATED, SULFATES, SODIUM SALTS (CAS: 68891-38-3)

Biodegradability : no degradability data is available, the substance is considered as not degrading quickly.

LAURYLMYRISTYL POLYGLYCOL ETHER (CAS: 68439-51-0)

Biodegradability : no degradability data is available, the substance is considered as not degrading quickly.

**12.3. Bioaccumulative potential**

No data available.

**12.4. Mobility in soil**

No data available.

**12.5. Results of PBT and vPvB assessment**

No data available.

**12.6. Other adverse effects**

No data available.

**SECTION 13 : DISPOSAL CONSIDERATIONS**

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

**13.1. Waste treatment methods**

Do not pour into drains or waterways.

**Waste :**

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

**Soiled packaging :**

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

**SECTION 14 : TRANSPORT INFORMATION**

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2019 - IMDG 2018 - ICAO/IATA 2019).

**14.1. UN number**

3267

**14.2. UN proper shipping name**

UN3267=CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S.  
(disodium metasilicate)

**14.3. Transport hazard class(es)**

- Classification :



8

**14.4. Packing group**

III

**14.5. Environmental hazards**

-

**MOTO WASH 1LX12 IPONE REF 800670 - A18410**

**14.6. Special precautions for user**

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	8	C7	III	8	80	5 L	274	E1	3	E

IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ	Stowage Handling	Segregation
	8	-	III	5 L	F-A, S-B	223 274	E1	Category A SW2	SGG18 SG35

IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ
	8	8	III	852	5 L	856	60 L	A3 A803	E1
	8	8	III	Y841	1 L	-	-	A3 A803	E1

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

**14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**

No data available.

**SECTION 15 : REGULATORY INFORMATION**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**- Classification and labelling information included in section 2:**

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2018/1480 (ATP 13)
- EU Regulation No. 1272/2008 amended by EU Regulation No. 2019/521 (ATP 12)

**- Container information:**

Packaging to be fitted with child-resistant fastenings (see EC Regulation No. 1272/2008, Annex II, Part 3).

Containers to be fitted with a tactile warning of danger (see EC Regulation No. 1272/2008, Annex II, Part 3).

**- Particular provisions :**

No data available.

**- Labelling for detergents (EC Regulation No. 648/2004,907/2006) :**

- less than 5 % : anionic surfactants
- less than 5 % : nonionic surfactants
- perfumes

**15.2. Chemical safety assessment**

The chemical safety assessment has not been carried out for this mixture.

**SECTION 16 : OTHER INFORMATION**

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

**Wording of the phrases mentioned in section 3 :**

H226	Flammable liquid and vapour.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

**Abbreviations :**

DNEL : Derived No-Effect Level

PNEC : Predicted No-Effect Concentration

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

**MOTO WASH 1LX12 IPONE REF 800670 - A18410**

---

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefährdungsklasse (Water Hazard Class).

GHS05 : Corrosion

PBT: Persistent, bioaccumulable and toxic.

vPvB : Very persistent, very bioaccumulable.

SVHC : Substances of very high concern.